Proxima DP9250 Projector
Technical and Functional Specifications

Display Technology	• 1.3" polysilicon TFT LCD x 3 with micro lens
Resolution	• XGA 1024 x 768
Resolutions Supported	• VGA (640 x 480) • SVGA (800 x 600) • XGA (1024 x 768) • SXGA (1280 x 1024, compressed)
Brightness	• 1400 ANSI lumens
Contrast Ratio	• 100:1 ANSI, 350:1 (full on,full off)
Computer Compatibility	• IBM PC, PS/2, Pentium and Compatibles • SUN, SGI, IBM, HP, DEC, and X-Terminals • Apple Macintosh,Power Macintosh, and PowerBook families
Video Compatibility	• NTSC, NTSC 4.3, PAL, PAL-M, SECAM
Sources	• 2 computer, 2 audio, 2 video, 1 S-video
H-Sync Range	• 15 to 100 KHz
V-Sync Range	• 50 to 100 Hz
Dot Clock	• 160 MHz
Horizontal Resolution	• 800 TV Lines
Aspect Ratio	• std:4:3 - wide:16:9
Image Size (Diagonal)	• 3.3 ft (1 m) to 25 ft (7.6 m)
Lens	• Power zoom and focus lens 1:3:1 ratio • Focal length: 48.4 mm to 62.8 mm, F 1.8 to F 2.1
Projection Distance (From Screen)	• 4.6 ft (1.4 m) to 35.4 ft (10.8 m)
Keystone Correction	• 11°
Number of Colors	• 16.7 million
Lamp	• 160 watt metal halide • Lamp life: 1,500 hours to 50% brightness
Audio	• 2W + 2W RMS stero
Remote Control	• Laser F/X wireless IR remote with mouse control and Laser pointer
Dimensions	• 6.1 in H x 10.7 in W x 16.3 in L • (15.4 cm H x 27.2 cm W x 41.2 cm L)
Weight	• 13.6 lbs (6.2 kg)
Power Consumption	• 250 watts
Power Requirements	• 100 to 120V / 220 to 240V at 50/60 Hz
Operating Temperature (Sea Level)	• 41° F (5° C) to 95° F (35° C)
Approvals	• FCC Class A (U.S), UL, c-UL (Canada), CE
Warranty	• Two years on parts and labor (excluding lamp)

Copyright © 1997-2004 InFocus Corporation.
All Rights Reserved.